



HENGZHUN

东莞力显仪器科技有限公司

DONG GUAN LIXIAN INSTRUMENT SCIENTIFIC CO.,LTD

Introduction

Name: HZ-6014 Vibration Test Machine



Equipment Overview:

Carton vibration test machine is based on the United States and European transport standards, and with reference to the United States of similar equipment to improve manufacturing. The use of eccentric bearings in rotating elliptical trajectories generated to simulate a car or ship the goods during transport the vibration of the collision. Test platform will be fixed on the eccentric bearing, when the eccentric bearing rotation, the test platform for the entire plane would produce an oval-shaped upper and lower front and rear movement, adjust the eccentric shaft with the rotation speed is equivalent to adjust the speed of motor vehicles or vessels.

Main Features:

Digital instrument display vibration frequency; synchronous belt transmission mute, very low noise; test items using clamping rail type, easy to operate, safe; machine using heavy-duty channel steel base with anti-vibration pad, easy installation, smooth operation, without Install ground pin screw; DC motor speed control, running smoothly, load capability; rotary vibration (commonly known as Valley-type).

Tel: +86 769-23388229

Fax:+86 769-23388227

Website: www.dglixian.com

E-mail: sales1@hengzhunx.com, sales2@hengzhunx.com

Adress:Xinhe Management of area, Wanjiang District, Dongguan city, Guangdong province, China



HENGZHUN

东莞力显仪器科技有限公司

DONG GUAN LIXIAN INSTRUMENT SCIENTIFIC CO.,LTD

To meet the criteria:

This instrument meets the following standards: GB / T 4857.7-92 "transport package fixed-frequency sinusoidal vibration test method"

Applications Industry:

The machine applies to toys, electronics, furniture, gifts, ceramics, packaging and other products packaged to simulate the transport tests, in line with the United States and European transport standards.

Technical parameter:

Model	HZ-6014A	HZ-6014B	HZ-6014C
Rated load	75 kg	150 kg	230 kg
Testing dimension	110*98 cm	130*120 cm	180*150cm
Maximum Acceleration	1.25g		
Frequency	Frequency of 2-5 Hz continuously adjustable		
Amplitude	25.4MM(1 Inch)		
Power	220 V60Hz		
Motor	Rotary DC motor		
Fence Height	33 cm	38 cm	42 cm
Dimension	120×110 cm	140×130 cm	190×160 cm
Gross	169 kg	288 kg	396 kg

Tel: +86 769-23388229

Fax:+86 769-23388227

Website: www.dglixian.com

E-mail: sales1@hengzhunx.com, sales2@hengzhunx.com

Adress:Xinhe Management of area, Wanjiang District, Dongguan city, Guangdong province, China