

<b>(Specification) : (7/0.08T*1P+D+AL+MY)*2P+7/0.08T*1P+7/0.20T*2C+F+AB16/9/0.08T OD:4.2</b>				
<b>(Component)</b>		<b>COMPONENT A</b>	<b>COMPONENT B</b>	<b>COMPONENT C</b>
<b>(Conductor)</b>	<b>(Constitution) AWG/mm</b>	7/0.08 (32AWG)	7/0.08(32AWG)	7/0.20(24AWG)
	<b>(Material)</b>	TINNED COPPER STRANDED	TINNED COPPER STRANDED	TINNED COPPER STRANDED
	<b>(Cabling OD) mm</b>	0.24(REF)	0.24(REF)	0.60(REF)
<b>(Insulation)</b>	<b>(NO of wire)</b>	2P	1P	2C
	<b>(Material)</b>	FOAM-PE-SKIN	HD-PE	HDPE
	<b>(OD) mm</b>	0.58±0.05	0.50±0.05	0.90±0.05
	<b>(Thickness)mm</b>	0.17(REF)	0.13(REF)	0.15(REF)
	<b>(Color)</b>	1. YELLOW&BLUE 2. ORANGE&PURPLE	3. WHITE&GREEN	4. RED 5. BLACK
<b>(Shield)</b>	<b>(Drain)</b>	7/0.08T(32AWG)	/	/
	<b>(AL/MYLAR)</b>	AL. FACE INSIDE	/	/
	<b>(Transparent mylar tape)</b>	TRANSPARENT MYLAR TAPE	/	/
	<b>(Filler)</b>	FILLER		
	<b>(AL/MYLAR)</b>	AL. FACE OUTSIDE		
	<b>(Constitution) N/mm</b>	16/9/0.08		
	<b>(Material)</b>	TINNED COPPER		
<b>(Jacket)</b>	<b>(Coverage) %</b>	85%		
	<b>(OD) mm</b>	4.20±0.20		
	<b>(Material)</b>	TPE(VW-1)		
	<b>(Thickness)mm</b>	0.50(REF)		
	<b>(Marking)</b>	NO MARKING		
	<b>(Hardness)A</b>	SHORE. A 80±3		
<b>(Color)</b>	WHITE			
<b>UL(Style)</b>				

<b>(Electric Characters) :</b>	<b>(Physical Characters) :</b>
1. Voltage rating: 30V 2. Temperature rating: 80°C 3. Spark test:AC- 1500V/In the air 4. Dielectric strength: AC-500V/1 sec MIN 5. Insulation resistance: FOAM-PE-SKIN/HD-PE DC-500V 100MΩ.KM MIN. at 20°C, 6. Conductor resistance. 32AWG-588 Ω/KM MAX at 20°C, 24AWG-93 Ω/KM MAX at 20°C.	

<b>(Diagram) :</b>	<b>(CUSTOMER'S SIGN) :</b>		
		(FULL APPROVED)	(REJECTED)
	(CUSTOMER'S SIGN)		
	(NOTE)		
<b>P-SHINE ELECTRONIC TECH LTD</b>			
APPROVE :		MPN: PSUSB3024232GLT	
AUDITING :		EDITION: S0081877	
DRAWING: XU		DATE: 2020/1/8	