



NOTE:

- TESTING CONDITIONS:
 - A: INSULATION RESISTANCE: 5MΩ;
 - B: VOLTAGE: DC300V/0.01S
 - C: CONDUCTOR RESISTANCE 3Ω;
 - D: ELECTRIC CURRENT: 5.0A MAX;
 - E: TRANSMISSION RATE: MORE THAN 700MB/S;
 - F: CABLE MUST BE OPEN/SHORT/MISWIRE 100% TEST.
- PACKING: 1PCS/PE-BAG
- ROHS 2.0

6	4	SCREWS: M2	
5	AR	OVER MOLDING: 45P PVC BLACK	
4	AR	INTERNAL MOLDING: PE	
3	1	USB 3.1 C TYPE MALE: GOLD PLATED CONTACTS, NICKEL PLATED SHELL, SEAMLESS STRETCH	+IC 332
2	1	USB 3.1 C TYPE MALE: GOLD PLATED CONTACTS, NICKEL PLATED SHELL, SEAMLESS STRETCH	
1	1	USB 3.1 CABLE (1/0.254T*1P+D+AL+HM)*4C+7/0.08T*1P+7/0.08T*4C+7/0.20T*2C+D+AB16/9/0.08T OD : 4.50mm	
NO	Q'TY	DESCRIPTION	REMARK

P-shine	P-SHINE ELECTRONIC TECH LTD		SCALE: NONE	UNIT: mm
DRAWING		P/N:		PAGE: 1/2
CHECKED		CUST P/N:		DWG NO: MF-GV0709
RECHECKED		SPEC: USB 3.1 C CABLE WITH DOUBLE SCREW LOCK		
APPROVED		RFQ NO.		