

## JZ-305 Top coating for exterior wall decoration

### Introduction:

JZ-305 adopts the international nano innovative formula, which is refined with acrylic ester as the base material. It has the lotus effect and has a weather resistance of up to 3-5 years. It has excellent resistance to acid and alkali, salt spray, and weather, which makes your exterior wall last beautiful. The coating film has the function of elastic heat insulation. It is a decorative material for exterior walls with multiple functions.

### Application:

Exterior wall decoration of hotels, villas, garden district, high-end office buildings, etc.

### Function:

Anti-UV radiation

Weather resistance of 3-5 years

Resistance to acid and alkali, salt spray, and aging

Resistance to mildew, algae, and stain;

### Suggested painting system:

High-performance interior wall putty 2 times;

Jointas Primer 1 time

Jointas JZ-305 2 times

### Physical parameters:

**Dilution:** Use clean water (not exceeding 20% of the total mass) to dilute, and stir evenly;

#### Theoretical paint consumption:

High elasticity: 6-8m<sup>2</sup>/kg/time (dry film thickness 50 microns);

Semigloss, matte: 12-14m<sup>2</sup>/kg/time (dry film thickness 30 microns); 100-130m<sup>2</sup>/barrel/twice

**Construction conditions:** Environment temperature >5°C; relative humidity <85%;

**Recoating time:** Under the condition of environment temperature 25°C, humidity <85%; Tack-free time: 30 minutes;

Recoating: 2 hours. Make appropriate adjustments according to the environment temperature and humidity.

**Luster:** High elasticity, semigloss, matte

**Color:** White or refer to color card.