

Model: NKR-PAC



AC output: Single cable&gun or socket for 7/22/43kw

Double cable&guns or sockets for 2*7/22/43kw



Specifications

Appearance	Dimension	H163*W28*T19cm
	Weight	53kg
	Cable length	≥4.2m(External line)
	Installation Method	Floor stand
	Box Material	Sheet metal
	Screen	5 inch LCD
Electrical Features	Input	Single phase:230VAC±10% Three phase:400VAC±10%
	Input frequency	50Hz/60Hz
	Rated power	Type2:7/22/43kw Type1:9kw
	Precision	Level 1

	Output Voltage	100VAC-400VAC+/-20%
	Output Current	Type2:7kw-single phase 32A 22kw-three phase 32A 43kw-three phase 64A Type1:9kw-single phase 40A
	Consumption	<2w
Functional Features	RCD	Type B:30ma ac and 6ma dc
	User Interface	Emergency Stop/LCD touch screen/LED indicator/RFID
	Safety Features	Overvoltage/undervoltage protection, overload protection, leakage protection, Overcurrent protection
Communication	Internet Interface	Ethernet(WIFI, 3g/4gLTE as optional)
	OCP	OCP 1.6J
Working environment	Working latitude	<2000m
	Working temperature	-30° C ~ +55° C
	Working humidity	5 % ~ 95%
	Protection level	IP55
	Cooling	Natural cooling
	Safety standards	IEC61851-1/2017
	Special protection	Anti-UV protection
LCD Panel	Panel size	55 inch
	Maximum resolution	1920x1080
	Brightness(nits)	2500nits

After-sale Service

1. One year warranty for all parts. If any parts break during the period, we will provide free replacement. Non-quality factor damage is not included.
2. One to one technical engineer support for installation&operation and communication connection assistance between your app and our OCPP platform.

Additional Accessories for Options

1. Wifi connection to Internet.
2. 3g/4g/GPRS connection to Internet.
3. Customized cable length.
4. Customized Box color and customized logo

For more charger and videos, welcome to visit:

Website: www.cnchargepoint.com