

Note: The photo is for illustration purposes only.
Please refer to outline drawing

■ Features

- Ultra Wide Band: 26-40GHz
- Low Insertion Loss: 2.5dB
- High Isolation
- Switch Type: Absorption

■ Applications

- Radar Systems
- Communication Systems
- Receivers Systems

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	26-40			GHz
Insertion Loss		2.5	3.6	dB
Loss Variation Over Temperature		0.003		dB/°C
Isolation	45	55		dB
Input VSWR		1.5	2.0	-
Output VSWR		1.5	2.0	-
Commutation time		50	100	ns
Power Handling (operational)			0.25	W
DC Current (Vcc=+5V/-5V)		50/50		mA
Control Logic TTL	0/+5			v
Impedance	50			Ω
Input Output Connector	2.92			
Material	Aluminium/Gold Painting			
Weight	50g			
Package Sealing	Standard sealing			

Environmental Conditions

Operational Temperature	-45°C~+85°C	Vibration	25g rms (15 degree 2KHz) endurance, 2 hour per axis
Storage Temperature	-55°C~+125°C	Shock	20G for 11msc half sin wave, 3 axis both directions
Executive Standard	MIL-STD-810G	Humidity	100% RH at 35c, 95%RH at 40°C

Absolute Maximum Ratings

Supply Bias Voltage	+/-10%
RF INPUT POWER	0.25W
ESD sensitivity (HBm)	Class 0, passed 150V




OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES



Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



TTL Control Voltages & VDD	
Stage	Bias Condition
VDD	+5V ($\pm 10\%$)
VEE	-5V ($\pm 10\%$)
Low	0 to 0.8Vdc
High	2.0 to +5.0Vdc

Truth Table	
Control TTL Input	Signal Path State
C1	
0	J0-J1
1	OFF